

Technical Data Sheet



Anglian 70mm White Knight In-line Sliding Door

Supply Chain		System designer Extruder Fabrication Installer	Anglian Anglian Anglian Anglian
	Material	Impact modified PVC-u	Standard
Frame	Size	Thickness (front to back) Depth	70mm to 100mm 60mm
	Threshold	PVC-u 60mm	Standard
	External Cill	85mm, 150mm, 180mm 225mm	Option
	Colour	Colour white Colour brown Colour brown/white	Standard Option Option
	Reinforcement	Galvanised Steel	Standard
	Standards	Quality	BS EN ISO 9001 Quality Management System
Environment		BS EN ISO 14001 Environmental Management System	Standard
Product		BBA Certificate BBA Resistance to Intrusion BS 7412 Fabrication and performance BS EN 12608 PVC-u Profiles BS EN 1279 Insulating Glass Units BS 12150 Safety Glass	Standard Standard Standard Standard Standard Standard
Performance		Weather	Strength and Stability -Safety Tested Strength and Stability -(Two Part) Water tightness Air permeability
	Sound	Noise Insulation 4-16-4 Noise insulation 4-14-6 Noise insulation 4-12-7	33 db 35 db 38 db
	Thermal	Whole window 'U' value standard (gas filled) Whole window 'U' value options to	1.6 W/M ₂ /K 1.4 W/M ₂ /K
Glazing	Bead System	Internal co-extruded beads with clearline gaskets	Standard
	Sealed Unit	SGG Planitherm Total 1.1 low-emissivity glazing 24mm sealed units Gas filled sealed units Glazing bars/leaded lights Safety Glazing toughened glass Safety Glazing laminated glass	Standard Standard Option Option Standard Option
Hardware	Locking System	Multi point locking system with shoot bolt and mushrooms	Standard