

Technical Data Sheet

Anglian 70mm White Knight In-line Sliding Door



Frame	Material	Impact modified PVC-u	Standard
	Size	Thickness (front to back) Depth	70mm to 100mm 60mm
	Threshold	PVC-u 60mm	Standard
	External Cill	85mm, 150mm, 180mm, 225mm	Option
	Colour	Colour white Colour brown Colour brown/white	Standard Option Option
	Reinforcement	Galvanised Steel (in accordance with BS 7412)	Standard
Standards	Quality	BS EN ISO 9001 Quality Management System	Standard
	Environment	BS EN ISO 14001 Environmental Management System	Standard
	Product	BBA Certificate BBA Security against intrusion BS 7412 Fabrication and performance BS EN 12608 PVC-u Profiles BS EN 1279 Insulating Glass Units BS 12150 Safety Glass Secured By Design	Standard Standard Standard Standard Standard Standard Option
	Weather	Strength and Stability - Safety Test Strength and Stability -(Two Part) Water tightness Air permeability	3000 Pa 1600 Pa 300 Pa 600 Pa
Sound	Noise insulation 4-16-4 Noise insulation 4-14-6 Noise insulation 4-12-7	33 db 35 db 38 db	
Glazing	Bead System	Internal co-extruded beads with clearline gaskets	Standard
	Sealed Unit	SGG Planitherm Total 1.1 low-emissivity glazing 24mm sealed units Gas filled sealed units Glazing bars/leaded lights Safety glazing toughened glass Safety glazing laminated glass	Standard Standard Option Option Standard Option
Hardware	Locking System	Multi point locking system with shoot bolt and mushrooms	Standard
	Ventilation	Through top rail of fixed leaf	Option
Supply Chain		System designer Extruder Fabrication Installer	Anglian Anglian Anglian Anglian

ITS339E(5/10)