

<b>Frame</b>	<b>Material</b>	Impact modified PVC-u	Standard
	<b>Size</b>	Thickness (front to back)	70mm
		Depth	77mm
	<b>External Cill</b>	85mm, 150mm, 180mm, 225mm	Option
	<b>Colour</b>	Colour white	Standard
Colour brown		Option	
Colour brown/white		Option	
<b>Reinforcement</b>	Galvanised Steel (in accordance with BS7412 to 1200Pa)	Standard	
<b>Standards</b>	<b>Quality</b>	BS EN ISO 9001 Quality Management System	Standard
	<b>Environment</b>	BS EN ISO 14001 Environmental Management System	Standard
	<b>Product</b>	BS 7412 Fabrication and Performance	Standard
		PAS24 Enhanced Security	Option
		BS EN 12608 PVC-u Profiles	Standard
BS EN 1279 Insulating Glass Units		Standard	
BS 12150 Safety Glass	Standard		
Secured By Design	Option		
<b>Performance</b>	<b>Weather</b>	Individual Opening Lights	1200 Pa
		Water tightness	300 Pa
Air permeability		600 Pa	
<b>Thermal</b>	Whole window 'U' value standard (gas filled)	1.6 W/M <sub>2</sub> /K	
	Whole window 'U' value options to	1.0 W/M <sup>2</sup> /K	
	Window Energy Rating standard	C	
	Window Energy Rating Options to	A	
<b>Glazing</b>	<b>Bead System</b>	Internal co-extruded beads with clearline gaskets	Standard
	<b>Sealed Unit</b>	Low-emissivity glazing	Standard
		24mm Sealed Units	Standard
		28mm Sealed Units	Option
		Triple Glazing	Option
		Gas filled sealed units	Standard
		Obscured Glazing	As Required
Safety glazing toughened glass		Option	
Safety glazing laminated glass	Option		
<b>Hardware</b>	<b>Locking System</b>	Trojan Sparta Tilt & Turn Handles	Standard
		Key Locking Handles	Option
		Face fixed locking gear	Standard
		Concealed locking gear	Option
		Enhanced security (PAS24)	Option
<b>Restrictors</b>	Maco Surface mounted	Option	
	Variable tilt device	Option	
<b>Ventilation</b>	Titon Select S13 Controllable Trickle Vents through top rail of opener	Standard	
<b>Supply Chain</b>		System designer	Anglian
		Extruder	Anglian
		Fabrication	Anglian
		Installer	Anglian